# LINED SIMPLEX

# Model 72 L

Tefzel<sup>®</sup> Lined Basket Strainer DN 25 to 150 (1" to 6")

Carbon Steel

These value added features:	Give these benefits
Tefzel <sup>®</sup> lined	High resistance to aggressive media
Quick open yoke and cover	Fast access to basket chamber
Large capacity basket	Longer service time, less cleaning
Flanged drain	Allows connection to lined piping
Integral mounting feet	Fully supported installation



Selection Chart						<b>Basket options:</b>
	Size	Body Material	End Connections	Seals Rating	Manal	
	DN 25 to 150	Tefzel <sup>®</sup> lined Carbon Steel	ANSI 150/DIN PN 10/16	Viton®	13.8 bar @ 38°C	Monel HASTELLOY Tefzel <sup>®</sup> coated

# "Y" TYPE

## Model 80 & 85

### "Y" Type Strainer

<sup>1</sup>/<sub>4</sub>" to 10" Carbon Steel or Stainless Steel

Simple and quick to empty

Reduced weight

#### These value added features: Give these benefits

Compact design Threaded drain plug

#### Also available:

Larger sizesRTJ FlangesMonel screensHigher pressure ratingsBlow down valve instead of standard drain connection



#### **Selection Chart**

Size	Body Material	End Connections	Cover	Rating	Seals	Model			
1/4" to 2"	Carbon Steel	Threaded NPT or 600lb Socket	Threaded	102 bar @ 38°C	Compressed, non-asbestos, synthetic fibre	85			
74 l0 Z	Stainless Steel			99 bar @ 38°C					
	Carbon Steel	ANSI 150	Bolted	19.6 bar @ 38°C					
1/ 1/ 1/01		ANSI 300		51 bar @ 38°C					
<sup>1</sup> / <sub>4</sub> " to 10"	Stainless Steel	ANSI 150		19 bar @ 38°C					
		ANSI 300		49.7 bar @ 38°C					
<sup>1</sup> / <sub>2</sub> " to 10"	Carbon Steel				102 bar @ 38°C				
<sup>1</sup> / <sub>2</sub> " to 6"	Stainless Steel	ANSI 600	51 600	99 bar @ 38°C		80			